

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878 Issue date: 27-2-2015 Revision date: 5-10-2015 Supersedes version of: 27-2-2015 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : OS-C-012-1 X-Treme Degreaser

Type of product : Detergent

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : For professional use only

Industrial

Use of the substance/mixture : Cleaning product

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

OMEGA-SKINZ / SOTT INTERNATIONAL BV De Donge 2c 5684 PX Best, The Netherlands

T +31 499 751 810

info@sott-international.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixtures/Substances: SDS EU > 2015: According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

Flammable liquids, Category 3

Specific target organ toxicity — Single exposure, Category 3, Narcosis

Specific target organ toxicity — Single exposure, Category 3, H335

Respiratory tract irritation

Specific target organ toxicity — Repeated exposure, Category 1

H372

Aspiration hazard, Category 1

H304

Hazardous to the aquatic environment — Chronic Hazard, Category 2

H411

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes damage to organs through prolonged or repeated exposure. May cause drowsiness or dizziness. May cause respiratory irritation. Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

2.2. Label elements

Hazard statements (CLP)

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)









GHS02

GHS07

SHS08

GHS09

Signal word (CLP) : Danger

Contains : Hydrocarbons, C9, aromatics; xylene; ethylbenzene; Hydrocarbons, C9-C12, n-alkanes,

isoalkanes, cyclics, aromatics (2-25%)

: H226 - Flammable liquid and vapour.

H304 - May be fatal if swallowed and enters airways.

H335 - May cause respiratory irritation. H336 - May cause drowsiness or dizziness.

H372 - Causes damage to organs through prolonged or repeated exposure.

H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 - Avoid breathing vapours, mist. P273 - Avoid release to the environment.

P301+P310+P331 - IF SWALLOWED: Immediately call a doctor, a POISON CENTER. Do

NOT induce vomiting.

P312 - Call doctor, a POISON CENTER if you feel unwell.

P391 - Collect spillage.

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	(EC-No.) 919-446-0 (REACH-no) 01-2119458049-33	≥ 50	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Hydrocarbons, C9, aromatics	(EC-No.) 918-668-5 (REACH-no) 01-2119455851-35	25 – 50	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
butanone; ethyl methyl ketone substance with national workplace exposure limit(s) (IE); substance with a Community workplace exposure limit	(CAS-No.) 78-93-3 (EC-No.) 201-159-0 (EC Index-No.) 606-002-00-3 (REACH-no) 01-2119457290-43	5 – 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

xylene substance with national workplace exposure limit(s) (IE); substance with a Community workplace exposure limit (Note C)	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32	1 – 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
mesitylene; 1,3,5-trimethylbenzene substance with national workplace exposure limit(s) (IE); substance with a Community workplace exposure limit	(CAS-No.) 108-67-8 (EC-No.) 203-604-4 (EC Index-No.) 601-025-00-5 (REACH-no) 01-2119463878-19	1 – 5	Flam. Liq. 3, H226 STOT SE 3, H335 Aquatic Chronic 2, H411
ethylbenzene substance with national workplace exposure limit(s) (IE); substance with a Community workplace exposure limit	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4 (REACH-no) 01-2119489370-35	1 – 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
mesitylene; 1,3,5-trimethylbenzene	(CAS-No.) 108-67-8 (EC-No.) 203-604-4 (EC Index-No.) 601-025-00-5 (REACH-no) 01-2119463878-19	(25 ≤C ≤ 100) STOT SE 3, H335

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Immediately flush skin or eyes (or both) with running water for at least 20 min. Call a

physician immediately.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center or a

doctor if you feel unwell.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness. Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after ingestion : Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour. Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained

breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Do not breathe

dust/fume/gas/mist/vapours/spray. Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection". Equip cleanup crew with proper

protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or

public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a

well-ventilated area.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the

product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Incompatible materials : Reacts violently with (strong) oxidizers.

7.3. Specific end use(s)

No additional information available

5-10-2015 (Version: 2.0) EN (English) 4/15

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butanone; ethyl methyl ketone (78-93-3)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Butanone	
IOEL TWA	600 mg/m³	
IOEL TWA [ppm]	200 ppm	
IOEL STEL	900 mg/m³	
IOEL STEL [ppm]	300 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Ireland - Occupational Exposure Limits		
Local name	Methyl ethyl ketone (MEK)	
OEL TWA [1]	600 mg/m³	
OEL TWA [2]	200 ppm	
OEL STEL	900 mg/m³	
OEL STEL [ppm]	300 ppm	
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)	
Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018	

xylene (1330-20-7)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Xylene, mixed isomers, pure	
IOEL TWA	221 mg/m³	
IOEL TWA [ppm]	50 ppm	
IOEL STEL	442 mg/m³	
IOEL STEL [ppm]	100 ppm	
Notes	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Ireland - Occupational Exposure Limits		
Local name	Xylene, mixed isomers	
OEL TWA [1]	221 mg/m³	
OEL TWA [2]	50 ppm	
OEL STEL	442 mg/m³	
OEL STEL [ppm]	100 ppm	
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)	
Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018	

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

mesitylene; 1,3,5-trimethylbenzene (108-67-8)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Mesitylene (Trimethylbenzenes)	
IOEL TWA	100 mg/m³	
IOEL TWA [ppm]	20 ppm	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Ireland - Occupational Exposure Limits		
Local name	Mesitylene (also 1,3,5 trimethylbenzene)	
OEL TWA [1]	100 mg/m³	
OEL TWA [2]	20 ppm	
Notes (IE)	IOELV (Indicative Occupational Exposure Limit Values)	
Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018	

ethylbenzene (100-41-4)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	Ethylbenzene	
IOEL TWA	442 mg/m³	
IOEL TWA [ppm]	100 ppm	
IOEL STEL	884 mg/m³	
IOEL STEL [ppm]	200 ppm	
Notes	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Ireland - Occupational Exposure Limits		
Local name	Ethylbenzene	
OEL TWA [1]	442 mg/m³	
OEL TWA [2]	100 ppm	
OEL STEL	884 mg/m³	
OEL STEL [ppm]	200 ppm	
Notes (IE)	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)	
Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018	

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Protective goggles. Gloves.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Hand protection:

The data are based on literature data and information from glove manufacturers or are derived by analogy from similar substances. It should be borne in mind that the useful life of a chemical glove can in practice be considerably shorter than the permeation time calculated in accordance with EN 374 due to many influence factors (eg temperature). The gloves must be replaced in the event of signs of wear. Gloves should be changed in case of contamination and after every chemical operation to prevent cross contamination. Dispose of the gloves in accordance with relevant national and local regulations. Chemical-resistant safety gloves (EN 374). Suitable materials with short contact resp. splashing. Recommended: at least permeation class 2, corresponding to> 30 minutes permeation time according to EN 374: Butyl rubber (IIR; ≥ 0.5 mm layer thickness)

Eye protection:

Protective goggles

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Provide local exhaust or general room ventilation to minimize mist and/or vapour concentrations. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Gas mask with filter type A

Personal protective equipment symbol(s):





Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : fluid.
Colour : Colourless.
Odour : Solvents.
Odour threshold : No data available

pH : Not applicable
Relative evaporation rate (butylacetate=1) : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available

Flash point : 40 °C

Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : Not applicable
Vapour pressure at 20 °C : No data available
Relative vapour density at 20 °C : No data available

Relative density : 0,81

Solubility : Practically not miscible.

Partition coefficient n-octanol/water (Log Pow) : No data available

Viscosity, kinematic : < 7 mm²/s
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour. Under fire conditions, hazardous fumes will be present.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Reacts with (strong) oxidizers.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

butanone; ethyl methyl ketone (78-93-3)	
LD50 oral rat	3460 mg/kg (OECD 423 method)
LD50 dermal rabbit	5000 mg/kg (OECD 402 method)
LC50 Inhalation - Rat [ppm]	> 7500
LC50 Inhalation - Rat (Vapours)	32 mg/l Source: RTECS

Hydrocarbons, C9, aromatics	
LD50 oral rat	3592 mg/kg
LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 6,193 mg/l/4h Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 Inhalation - Rat (Vapours)	> 6,193 mg/l/4h

xylene (1330-20-7)	
LD50 oral rat	3523 mg/kg Source: ECHA
LD50 dermal rabbit	12126 mg/kg bodyweight Animal: rabbit, Animal sex: male

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

mesitylene; 1,3,5-trimethylbenzene (108-67-8)	
LD50 oral rat	6000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EU Method B.1 (Acute Toxicity (Oral)), 95% CL: 4920 - 7320
LC50 Inhalation - Rat	> 10,2 mg/l/4h Animal: rat
LC50 Inhalation - Rat (Dust/Mist)	24 mg/l Source: RTECS

ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg Source: ECHA, HSDB
LD50 dermal rabbit	15400 mg/kg Source: ECHA, ChemIDPLUS

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
LD50 oral rat	> 15000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 Inhalation - Rat	> 13,1 mg/l Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation : Not classified pH: Not applicable

Serious eye damage/irritation : Not classified pH: Not applicable

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

xylene (1330-20-7)

IARC group 3 - Not classifiable

ethylbenzene (100-41-4)

IARC group 2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness. May cause respiratory irritation.

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

butanone; ethyl methyl ketone (78-93-3)

NOAEC (inhalation, rat, vapour, 90 days) 5014 mg/l

Hydrocarbons, C9, aromatics

NOAEL (oral, rat, 90 days)

600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

xylene (1330-20-7)

LOAEL (oral, rat, 90 days)

150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408
(Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)

mesitylene; 1,3,5-trimethylbenzene (108-67-8)

NOAEL (oral, rat, 90 days)

600 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

NOAEC (inhalation, rat, vapour, 90 days)	1,8 mg/l air Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
ethylbenzene (100-41-4)	
NOAEL (oral, rat, 90 days)	75 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90- Day Oral Toxicity in Rodents)

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
NOAEL (dermal, rat/rabbit, 90 days)	≥ 495 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Aspiration hazard : May be fatal if swallowed and enters airways.

600-T800 Industrial Degreaser	
Viscosity, kinematic	< 7 mm²/s

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : T

(chronic)

: Toxic to aquatic life with long lasting effects.

butanone; ethyl methyl ketone (78-93-3)	
LC50 - Fish [1]	2993 mg/l Test organisms (species): Pimephales promelas
EC50 - Crustacea [1]	308 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	1972 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	2029 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

Hydrocarbons, C9, aromatics	
LC50 - Fish [1]	9,2 mg/l 96h (Reference has been taken from the toxicological data of a similar product)
EC50 - Crustacea [1]	3,2 mg/l 48h (Reference has been taken from the toxicological data of a similar product)
EC50 72h - Algae [1]	0,42 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0,29 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	2,9 mg/l 72h (Reference has been taken from the toxicological data of a similar product)

xylene (1330-20-7)	
LC50 - Fish [1]	2,6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 3,4 mg/l Test organisms (species): Ceriodaphnia dubia
NOEC chronic fish	> 1,3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

mesitylene; 1,3,5-trimethylbenzene (108-67-8)	
LC50 - Fish [1]	12,52 mg/l Test organisms (species): Carassius auratus
EC50 - Crustacea [1]	6,01 mg/l Source: ECOTOX
NOEC (chronic)	0,4 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

ethylbenzene (100-41-4)	
LC50 - Fish [1]	5,1 mg/l Test organisms (species): Menidia menidia
EC50 72h - Algae [1]	4,9 mg/l Test organisms (species): Skeletonema costatum
EC50 72h - Algae [2]	5,4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	7,7 mg/l Test organisms (species): Skeletonema costatum
EC50 96h - Algae [2]	3,6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	1,7 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'
NOEC (chronic)	0,96 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
EC50 72h - Algae [1]	0,94 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0,53 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	1,2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	0,58 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

12.2. Persistence and degradability

butanone; ethyl methyl ketone (78-93-3)	
Persistence and degradability	Readily biodegradable in water.

Hydrocarbons, C9, aromatics	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

butanone; ethyl methyl ketone (78-93-3)	
Bioconcentration factor (BCF REACH) 3 (calculated value)	
Partition coefficient n-octanol/water (Log Pow)	0,3

xylene (1330-20-7)	
Partition coefficient n-octanol/water (Log Pow)	3,15 Source: HSDB

mesitylene; 1,3,5-trimethylbenzene (108-67-8)	
Partition coefficient n-octanol/water (Log Pow)	3,42 Source: ICSC

ethylbenzene (100-41-4)	
Partition coefficient n-octanol/water (Log Pow)	3,15 Source: HSDB

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

12.4. Mobility in soil

xylene (1330-20-7)

Mobility in soil 537 Source: ECHA

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR

14.1. UN number

UN-No. (ADR) : UN 1993

14.2. UN proper shipping name

Proper Shipping Name (ADR) : FLAMMABLE LIQUID, N.O.S.

Transport document description (ADR) : UN 1993 FLAMMABLE LIQUID, N.O.S. (Hydrocarbons, C9-C12, n-alkanes, isoalkanes,

cyclics, aromatics (2-25%); Hydrocarbons, C9, aromatics), 3, III, (D/E),

ENVIRONMENTALLY HAZARDOUS

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3



14.4. Packing group

Packing group (ADR) : III

14.5. Environmental hazards

Dangerous for the environment : Yes

Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1 Hazard identification number (Kemler No.) : 30

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Orange plates

30 1993

Tunnel restriction code (ADR)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following res	strictions are applicable according to Annex X\	/II of the REACH Regulation (EC) No 1907/2006:
Reference code	Applicable on	Entry title or description
3(a)	600-T800 Industrial Degreaser; butanone; ethyl methyl ketone; Hydrocarbons, C9, aromatics; xylene; mesitylene; 1,3,5-trimethylbenzene; ethylbenzene; Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	600-T800 Industrial Degreaser; butanone; ethyl methyl ketone; Hydrocarbons, C9, aromatics; xylene; mesitylene; 1,3,5-trimethylbenzene; ethylbenzene; Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	600-T800 Industrial Degreaser; Hydrocarbons, C9, aromatics; xylene; mesitylene; 1,3,5-trimethylbenzene; Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	600-T800 Industrial Degreaser; butanone; ethyl methyl ketone; Hydrocarbons, C9, aromatics; xylene; mesitylene; 1,3,5-trimethylbenzene; ethylbenzene; Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Detergent Regulation (648/2004/EC): Labelling of contents:	
Component	%
aliphatic hydrocarbons	≥30%
aromatic hydrocarbons	15-30%

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out for the substance or the mixture by the supplier

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 16: Other information

Indication of changes:			
Section	Changed item	Change	Comments
	Issue date	Modified	
	Revision date	Added	
	Supersedes	Added	
2.1	Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]	Removed	
3.2	Composition/information on ingredients	Modified	
8.1	Exposure limit values	Modified	

Abbreviations and acro	nyms:
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class



Safety Data Sheet

Copy Mattor (Repulation (EU) 2020/878

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3 OMEGA-SKINZ / SOTT INTERNATION	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
D-t 2 /25 nge 2c	Highly flammable liquid and vapour.
5684 PX Best, The Netherlands H226 T +31 499 751 810	Flammable liquid and vapour.
in in international.com	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet applicable for : IE regions

Mixtures/Substances: SDS EU > 2015: According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.